


TEST REPORT



Applicant	Flashbay Electronics
Address	Blgd b & C Xi Feng Cheng IND Zone, No.2 FuYuan Road He Ping, Village, FuYong Town, ShenZhen, China.

Manufacturer or Supplier	Flashbay Electronics	
Address	Blgd b & C Xi Feng Cheng IND Zone, No.2 FuYuan Road He Ping, Village, FuYong Town, ShenZhen, China.	
Product	Bluetooth speaker	
Brand Name	N/A	
Model	Cube	
Additional Model & Model Difference	N/A	
Date of tests	Mar. 20, 2017 ~ May. 16, 2017	

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

AS/NZS CISPR 32:2015

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Chris Chen Manager / EMC Department
	
	Date: May. 17, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Table of Contents

- RELEASE CONTROL RECORD3
- 1 SUMMARY OF TEST RESULTS4
 - 1.1 MEASUREMENT UNCERTAINTY4
 - 1.2 MODIFICATION RECORD4
- 2 GENERAL INFORMATION.....5
 - 2.1 GENERAL DESCRIPTION OF EUT.....5
 - 2.2 DESCRIPTION OF TEST MODES.....6
 - 2.3 TEST PROGRAM USED AND OPERATION DESCRIPTIONS.....6
 - 2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS6
 - 2.5 DESCRIPTION OF SUPPORT UNITS.....7
- 3 CONDUCTED EMISSION FROM THE AC MAINS POWER PORT8
 - 3.1 LIMITS8
 - 3.2 TEST INSTRUMENT.....8
 - 3.3 TEST ARRANGEMENT8
 - 3.4 TEST SETUP9
 - 3.5 SUPPLEMENTARY INFORMATION9
 - 3.6 TEST RESULTS.....10
- 4 RADIATED EMISSION MEASUREMENT12
 - 4.1 LIMITS12
 - 4.2 OF RADIATED EMISSION MEASUREMENT12
 - 4.3 TEST INSTRUMENTS14
 - 4.4 TEST PROCEDURE15
 - 4.5 TEST SETUP17
 - 4.6 SUPPLEMENTARY INFORMATION17
 - 4.7 TEST RESULTS (BELOW 1G).....18
- 5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....21
- 6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....24



**BUREAU
VERITAS**

Test Report No.: CT170320N019

RELEASE CONTROL RECORD

Issue No.	Description	Date Issued
CT170320N019	Original release	May. 17, 2017



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

Emission			
Standard	Test Item	Result	Remarks
AS/NZS CISPR 32: 2015	Conducted test	PASS	Minimum passing margin is -4.17dB at 0.65392 MHz
	Radiated emission 30-1000 MHz	PASS	Meets Limits Minimum passing margin is -7.34dB at 97.172MHz
	Radiated test (1GHz ~ 6GHz)	PASS	Meets Limits Minimum passing margin is -11.13dB at 4057.050MHz

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Mains Terminal Disturbance Voltage Test	0.15MHz ~ 30MHz	+ /-2.70 dB
Radiated Disturbance Test	30MHz ~ 1000MHz	+ /-4.06 dB
	1GHz ~ 6GHz	+/- 4.58 dB

1.2 MODIFICATION RECORD

There were no modifications required for compliance.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth speaker
TEST MODEL	Cube
ADDITIONAL MODEL	N/A
POWER SUPPLY	DC 3.7V from Li-ion Battery or DC from USB Host Unit.
CABLE SUPPLIED	USB Line: Unshielded, Detachable, 0.25m Aux In line: Unshielded, Detachable, 0.5m
HIGHEST OPERATION FREQUENCY	2480MHz

NOTE:

1. For the test results, the EUT had been tested with all conditions. But only the worst case was showed in test report.
2. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
3. Please refer to the EUT photo document (Reference No.: 170320N019) for detailed product photo.



2.2 DESCRIPTION OF TEST MODES

The EUT was tested under the following modes' the final worst mode were marked in boldface and recorded in this report.

◆ FOR CONDUCTED EMISSION TEST

Description of Test Mode	Test Voltage
AUX In+ Charging	DC5V from USB Host Unit
BT Link Normal Working+ Charging	DC5V from USB Host Unit

◆ FOR RADIATED EMISSIONS TEST (BELOW 1GHz)

Description of Test Mode	Test Voltage
AUX In+ Charging	DC5V from USB Host Unit
AUX In	DC 3.7V from Battery
BT Link Normal Working+ Charging	DC5V from USB Host Unit
BT Link Normal Working	DC 3.7V from Battery

◆ FOR RADIATED DISTURBANCE TEST (ABOVE 1GHz)

Description of Test Mode	Test Voltage
BT Link Normal Working+ Charging	DC5V from USB Host Unit

2.3 TEST PROGRAM USED AND OPERATION DESCRIPTIONS

- a. Turned on the power of all equipment.
- b. EUT was operated according to the type description in manufacturer's specifications or the User's Manual.

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to the specifications of the manufacturers, the EUT must comply with the requirements of the following standards:

AS/NZS CISPR 32:2015

All applicable tests have been performed and recorded as per the above standards.



2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an dependent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Adapter	APPLE	A1299	N/A	N/A
2	Adapter	N/A	DC 5V 1A	N/A	N/A
3	Mobile Phone	APPLE	A1332	CP7P0NTT79X9TN1	N/A
4	Mobile Phone	Apple	ML7F2CH/A	C6KQKXLAGRY8	N/A

NO.	CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1~4	N/A



3 CONDUCTED EMISSION FROM THE AC MAINS POWER PORT

3.1 LIMITS

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

- Notes: 1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases linearly with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

3.2 TEST INSTRUMENT

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,17	Apr. 04,18
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 06,17	Mar. 05,18
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,17	Apr. 04,18
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 04,17	Jan. 03,18
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed at Shielded Room 553.


3.3 TEST ARRANGEMENT

- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The test results of conducted emissions at mains ports are recorded of six worst margins for quasi-peak (mandatory) [and average (if necessary)] values against the limits at frequencies of interest unless the margin is 20 dB or greater.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.



3.4 TEST SETUP



- Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.


3.5 SUPPLEMENTARY INFORMATION

N/A

3.6 TEST RESULTS


TEST MODE		BT Link Normal Working + Charging								
TEST VOLTAGE		DC5V from USB Host Unit			6dB BANDWIDTH		9 kHz			
ENVIRONMENTAL CONDITIONS		25deg. C, 47% RH			TESTED BY: Yang					
PHASE OF POWER: LINE (L)										
No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.41744	9.85	35.17	31.37	45.02	41.22	57.50	47.50	-12.48	-6.28
2	0.65392	9.70	34.19	32.13	43.89	41.83	56.00	46.00	-12.11	-4.17
3	0.77023	9.69	32.09	27.43	41.78	37.12	56.00	46.00	-14.22	-8.88
4	1.96649	9.89	31.54	25.70	41.43	35.59	56.00	46.00	-14.57	-10.41
5	3.16500	10.00	29.53	21.69	39.53	31.69	56.00	46.00	-16.47	-14.31
6	18.78900	9.89	27.50	19.01	37.39	28.90	60.00	50.00	-22.61	-21.10

REMARKS: The emission levels of other frequencies were very low against the limit.



TEST MODE		BT Link Normal Working + Charging								
TEST VOLTAGE		DC5V from USB Host Unit		6dB BANDWIDTH		9 kHz				
ENVIRONMENTAL CONDITIONS		25deg. C, 47% RH		TESTED BY: Yang						
PHASE OF POWER: NEUTRAL (N)										
No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.41087	9.73	28.81	17.70	38.54	27.43	57.63	47.63	-19.09	-20.20
2	0.65392	9.76	29.97	20.05	39.73	29.81	56.00	46.00	-16.27	-16.19
3	0.77023	9.78	26.68	15.82	36.46	25.60	56.00	46.00	-19.54	-20.40
4	1.96350	9.81	26.16	14.50	35.97	24.31	56.00	46.00	-20.03	-21.69
5	4.47002	9.84	22.92	9.88	32.76	19.72	56.00	46.00	-23.24	-26.28
6	18.85650	9.76	24.84	15.13	34.60	24.89	60.00	50.00	-25.40	-25.11

REMARKS: The emission levels of other frequencies were very low against the limit.





4 RADIATED EMISSION MEASUREMENT

4.1 LIMITS

4.2 OF RADIATED EMISSION MEASUREMENT

FOR FREQUENCY BELOW 1000 MHz

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 10m)
	Quasi-Peak dBuV/m	Quasi-Peak dBuV/m
30 – 230	40	30
230 – 1000	47	37

FREQUENCY (MHz)	Class A (at 3m)	Class B (at 3m)
	Quasi-Peak dBuV/m	Quasi-Peak dBuV/m
30 – 230	50	40
230 – 1000	57	47

For FM receivers

Distance (m)	Source	Frequency Range (MHz)	Limits dB (uV/m)	
			Quasi-peak	
10	Local oscillator	≤1000	Fundamental	50
		30 to 300	Harmonics	42
		300 to 1000	Harmonics	46
	Other	30 to 230		30
		230 to 1000		37
3	Local oscillator	≤1000	Fundamental	60
		30 to 300	Harmonics	52
		300 to 1000	Harmonics	56
	Other	30 to 230		40
		230 to 1000		47

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	Up to 5 times of the highest frequency or 6 GHz, whichever is less

FOR FREQUENCY ABOVE 1000 MHz

FREQUENCY (GHz)	Class A (dBuV/m) (at 3m)		Class B (dBuV/m) (at 3m)	
	PEAK	AVERAGE	PEAK	AVERAGE
1 to 3	76	56	70	50
3 to 6	80	60	74	54

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
 3. All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



4.3 TEST INSTRUMENTS

FREQUENCY RANGE BELOW 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101564	Feb. 27,17	Feb. 26,18
EMI Test Receiver	Rohde&Schwarz	ESCI	101418	Feb. 27,17	Feb. 26,18
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-555	Nov. 13, 16	Nov. 12, 17
Trilog-Broadband Antenna	SCHWARZBECK	VULB 9168	9168-554	Dec. 17, 16	Dec. 16, 17
Signal Amplifier	Agilent	8447D	2944A10488	Jun. 25,16	Jun. 24,17
Signal Amplifier	Agilent	8447D	2944A11174	Jun. 25,16	Jun. 24,17
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m*8.8m	NSEMC006	Mar. 06,17	Mar. 05,18
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

- NOTES:** 1. The test was performed in 10m Chamber.
 2. The calibration interval of the above test instruments is 12 and 24 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

FREQUENCY RANGE ABOVE 1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Horn Antenna	ETS-Lindgren	3117	00085519	Dec. 30, 15	Dec. 29, 17
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 15,17	Mar. 14,18
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101003	Apr. 05,17	Apr. 04,18
Broadband Preamplifier	SCHWARZBECK	BBV9718	266	Mar. 21,17	Mar. 20,18
Pre-Amplifier (100MHz-26.5GHz)	EMCI	EMC 012645	980077	May 04,17	May 03,18
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 04,16	Nov. 03,17
Test Software	ADT	ADT_Radiated_V8.7.07	N/A	N/A	N/A

- NOTES:** 1. The test was performed in 10m Chamber.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.4 TEST PROCEDURE

<Frequency Range below 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Emission level – Limit value.



<Frequency Range above 1GHz>

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna can be varied from one meter-to four meters, the height of adjustment depends on the EUT height and the antenna 3dB beamwidth both, to detect the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test receiver/spectrum was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.


NOTE:

1. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average detection (AV) at frequency above 1GHz.
2. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
3. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
6. Margin value = Emission level – Limit value.




4.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



* : depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3


4.6 SUPPLEMENTARY INFORMATION

The more stringent measurement method of paragraph 8.3.2 in ANSI C63.4:2014 was applied for the test.

4.7 TEST RESULTS (BELOW 1G)


TEST MODE		BT Link Normal Working + Charging						
FREQUENCY RANGE		30-1000 MHz		DETECTOR FUNCTION & BANDWIDTH		Quasi-Peak, 120kHz		
ENVIRONMENTAL CONDITIONS		23deg. C, 52% RH		TESTED BY: Sook				
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	36.936	-9.77	25.77	16.00	30.00	-14.00	400	36
2	96.497	-13.38	27.01	13.63	30.00	-16.37	400	13
3	166.777	-9.75	25.01	15.26	30.00	-14.74	200	288
4	244.817	-9.53	24.65	15.12	37.00	-21.88	200	204
5	282.213	-8.39	24.71	16.32	37.00	-20.68	400	330
6	342.792	-6.86	24.16	17.30	37.00	-19.70	400	113

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.



TEST MODE		BT Link Normal Working + Charging						
FREQUENCY RANGE		30-1000 MHz			DETECTOR FUNCTION & BANDWIDTH		Quasi-Peak, 120kHz	
ENVIRONMENTAL CONDITIONS		23deg. C, 52% RH			TESTED BY: Sook			
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 M								
No.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	54.614	-8.22	26.68	18.46	30.00	-11.54	300	186
2	97.172	-13.29	35.95	22.66	30.00	-7.34	100	87
3	131.244	-12.07	28.24	16.17	30.00	-13.83	100	84
4	184.472	-9.76	25.19	15.43	30.00	-14.57	300	357
5	210.662	-9.28	26.45	17.17	30.00	-12.83	300	326
6	242.915	-6.88	24.58	17.70	37.00	-19.30	300	347

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 30MHz to 1000MHz.
 4. Only emissions significantly above equipment noise floor are reported.





TEST MODE	BT Link Normal Working + Charging	FREQUENCY RANGE	Above 1G
TEST VOLTAGE	DC5V from USB Host Unit	DETECTOR FUNCTION & RESOLUTION BANDWIDTH	Peak/Average,1MHz
ENVIRONMENTAL CONDITIONS	21deg. C, 54% RH	TESTED BY: Wang	

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	3582.450 PK	2.04	58.36	60.40	74.00	-13.60	300	15
2	3582.450 AV	2.04	38.53	40.57	54.00	-13.43	300	15
3	4157.500 PK	3.28	57.24	60.52	74.00	-13.48	200	285
4	4157.500 AV	3.28	38.62	41.90	54.00	-12.10	200	285
5	4983.600 PK	4.09	55.90	59.99	74.00	-14.01	100	57
6	4983.600 AV	4.09	36.78	40.87	54.00	-13.13	100	57
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	Freq. (MHz)	Correction Factor (dB/m)	Raw Value (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)
1	3564.500 PK	2.00	58.42	60.42	74.00	-13.58	100	24
2	3564.500 AV	2.00	39.52	41.52	54.00	-12.48	100	24
3	4057.050 PK	3.11	58.88	61.99	74.00	-12.01	200	244
4	4057.050 AV	3.11	39.76	42.87	54.00	-11.13	200	244
5	4683.500 PK	3.95	56.87	60.82	74.00	-13.18	100	44
6	4683.500 AV	3.95	35.45	39.40	54.00	-14.60	100	44

- REMARKS:**
1. Peak detector quick scan is showed on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
 2. Negative sign (-) in the margin column signify levels below the limit.
 3. Frequency range scanned: 1GHz to 6GHz.
 4. Only emissions significantly above equipment noise floor are reported.





5 PHOTOGRAPHS OF THE TEST CONFIGURATION



CONDUCTED EMISSION TEST



RADIATED EMISSION TEST (<30MHz-1GHz>)



RADIATED EMISSION TEST <Above 1GHz>





**BUREAU
VERITAS**

Test Report No.: CT170320N019

6 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

END