



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan
District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM160400216001
Page: 1 of 20

TEST REPORT

Application No.: SZEM1604002160BA
Applicant: Flashbay Electronics
Address of Applicant: Blag b & C Xi Feng Cheng IND Zone, No.2 FuYuan Road He Ping, Village, FuYuan Town, ShenZhen
Manufacturer: Flashbay Electronics
Address of Manufacturer: Blag b & C Xi Feng Cheng IND Zone, No.2 FuYuan Road He Ping, Village, FuYuan Town, ShenZhen
Factory: Flashbay Electronics
Address of Factory: Blag b & C Xi Feng Cheng IND Zone, No.2 FuYuan Road He Ping, Village, FuYuan Town, ShenZhen
Equipment Under Test (EUT):
EUT Name: power bank
Model No.: Card
Standards: AS/NZS CISPR 22:2009+A1:2010
Date of Receipt: 2016-04-08
Date of Test: 2016-04-11
Date of Issue: 2016-04-27

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



2 Test Summary

Item	Standard	Method	Class	Result
Conducted Disturbance at Mains Terminals (150kHz-30MHz)	AS/NZS CISPR 22:2009+A1:2010	AS/NZS CISPR 22:2009+A1:2010	Class B	Pass
Radiated Disturbance (30MHz-1GHz)	AS/NZS CISPR 22:2009+A1:2010	AS/NZS CISPR 22:2009+A1:2010	Class B	Pass



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 DETAILS OF E.U.T.	4
4.2 DESCRIPTION OF SUPPORT UNITS.....	4
4.3 STANDARDS APPLICABLE FOR TESTING	5
4.4 TEST LOCATION	6
4.5 TEST FACILITY	6
4.6 DEVIATION FROM STANDARDS.....	6
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	6
5 EQUIPMENT LIST.....	7
6 EMISSION TEST RESULTS.....	9
6.1 CONDUCTED DISTURBANCE AT MAINS TERMINALS(150KHZ-30MHZ)	9
6.1.1 E.U.T. Operation.....	9
6.1.2 Test Setup.....	9
6.1.3 Measurement Data.....	9
6.2 RADIATED DISTURBANCE(30MHZ-1GHZ)	12
6.2.1 E.U.T. Operation.....	12
6.2.2 Measurement Data.....	12
7 PHOTOGRAPHS.....	15
7.1 CONDUCTED DISTURBANCE AT MAINS TERMINALS(150KHZ-30MHZ) TEST SETUP	15
7.2 RADIATED DISTURBANCE(30MHZ-1GHZ) TEST SETUP.....	15
7.3 EUT CONSTRUCTIONAL DETAILS	16-20



4.3 Standards Applicable for Testing

Table 1 : Tests Carried Out Under AS/NZS CISPR 22:2009+A1:2010

Method	Item	Status
AS/NZS CISPR 22:2009+A1:2010	Conducted Disturbance at Mains Terminals (150kHz-30MHz)	√
AS/NZS CISPR 22:2009+A1:2010	Conducted Disturbance at Telecommunication Port (150kHz-30MHz)	×
AS/NZS CISPR 22:2009+A1:2010	Radiated Disturbance(30MHz-1GHz)	√
AS/NZS CISPR 22:2009+A1:2010	Radiated Disturbance(above 1GHz)	×

- × Indicates that the test is not applicable
√ Indicates that the test is applicable



4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

•CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

• FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

• Industry Canada (IC)

The the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-3.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Disturbance at Mains Terminals(150kHz-30MHz)						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2015-05-13	2016-05-13
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-09	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2015-05-13	2016-05-13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2015-08-30	2016-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2015-08-30	2016-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2015-08-30	2016-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2015-05-13	2016-05-13
8	Coaxial Cable	SGS	N/A	SEL0025	2015-05-13	2016-05-13

Radiated Disturbance(30MHz-1GHz)						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEL0303	2015-08-01	2016-08-01
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEL0175	2015-05-13	2016-05-13
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0288	2015-05-13	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0275	2015-05-13	2016-05-13
6	Coaxial cable	SGS	N/A	SEL0274	2015-05-13	2016-05-13
7	Trilog-Broadband Antenna(30M-1GHz)	Schwarzbeck	VULB9168	SEM003-17	2015-10-17	2018-10-17
8	Pre-amplifier	Sonoma Instrument Co	310N	SEL0298	2015-05-13	2016-05-13



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160400216001

Page: 8 of 20

General used equipment						
Item	Equipment	Manufacturer	Model No	Inventory No	Cal. date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Humidity/Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0101	2015-10-12	2016-10-12
2	Humidity/Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0102	2015-10-12	2016-10-12
3	Humidity/Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0103	2015-10-12	2016-10-12
4	Barometer	Chang Chun Meteorological Industry Factory	DYM3	SEL0088	2015-05-13	2016-05-13

6 Emission Test Results

6.1 Conducted Disturbance at Mains Terminals(150kHz-30MHz)

Test Requirement:	AS/NZS CISPR 22:2009+A1:2010
Test Method:	AS/NZS CISPR 22:2009+A1:2010
Frequency Range:	150kHz to 30MHz
Limit:	
0.15M-0.5MHz	66dB(μV)-56dB(μV) quasi-peak, 56dB(μV)-46dB(μV) average
0.5M-5MHz	56dB(μV) quasi-peak, 46dB(μV) average
5M-30MHz	60dB(μV) quasi-peak, 50dB(μV) average
Detector:	Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar


Pretest these mode to find the worst case:

- a: Charge mode, keep EUT being charged with adapter.
- c: Charge and discharge mode, keep EUT being charged with adapter and discharging to the resistor.

The worst case for final test:

- a: Charge mode, keep EUT being charged with adapter.

6.1.2 Test Setup



6.1.3 Measurement Data


An initial pre-scan was performed with peak detector. Quasi-Peak or Average measurement were performed at the frequencies with maximized peak emission were detected.



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160400216001
Page: 10 of 20

Mode:a;Line:Live Line



Site : Shielding Room
Condition: CE Line
Job No. : 2160BA
Test Mode: a


	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Over Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.25	0.06	9.84	28.08	37.98	51.91	-13.93	Peak
2	0.54	0.05	9.87	27.09	37.01	46.00	-8.99	Peak
3	1.50	0.04	9.93	28.80	38.77	46.00	-7.23	Peak
4	4.03	0.10	10.08	29.34	39.52	46.00	-6.48	Peak
5	10.73	0.59	10.15	28.91	39.65	50.00	-10.35	Peak
6	22.18	1.69	10.10	30.50	42.29	50.00	-7.71	Peak



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160400216001
Page: 11 of 20

Mode:a;Line:Neutral Line



Site : Shielding Room
Condition: CE Neutral
Job No. : 2160BA
Test Mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.26	0.06	9.86	27.78	37.70	51.51	-13.81 Peak
2	0.95	0.03	10.01	29.72	39.76	46.00	-6.24 Peak
3	2.01	0.04	10.12	25.99	36.15	46.00	-9.85 Peak
4	5.11	0.13	10.13	28.42	38.68	50.00	-11.32 Peak
5	12.85	0.77	10.18	28.65	39.60	50.00	-10.40 Peak
6	24.66	1.86	10.03	31.04	42.93	50.00	-7.07 Peak



6.2 Radiated Disturbance(30MHz-1GHz)

Test Requirement:	AS/NZS CISPR 22:2009+A1:2010
Test Method:	AS/NZS CISPR 22:2009+A1:2010
Frequency Range:	30MHz to 1GHz
Limit:	
30MHz-230MHz	30 dB(μ V/m) quasi-peak
230MHz-1GHz	37 dB(μ V/m) quasi-peak
Detector:	Peak for pre-scan (120kHz resolution bandwidth) 30M to 1000MHz

6.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.0 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar

	a: Charge mode, keep EUT being charged with adapter.
Pretest these mode to find the worst case:	b: Discharge mode, keep EUT discharging to the resistor.
	c: Charge and discharge mode, keep EUT being charged with adapter and discharging to the resistor.
The worst case for final test:	c: Charge and discharge mode, keep EUT being charged with adapter and discharging to the resistor.

6.2.2 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.

Mode:c;Polarization:Horizontal



Condition: 10m Horizontal
Job No. : 2160BA
Test Mode: c


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	156.46	7.48	13.40	32.80	26.18	14.26	30.00	-15.74
2	226.89	7.74	10.59	32.80	29.74	15.27	30.00	-14.73
3	312.18	8.08	13.01	32.79	27.45	15.75	37.00	-21.25
4	701.76	9.16	20.14	32.80	28.18	24.68	37.00	-12.32
5	779.61	9.25	21.09	32.72	28.00	25.62	37.00	-11.38
6 pp	922.52	9.51	22.53	32.60	27.09	26.53	37.00	-10.47



**SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch**

Report No.: SZEM160400216001
Page: 14 of 20

Mode:c;Polarization:Vertical



Condition: 10m Vertical
Job No. : 2160BA
Test Mode: c

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	104.54	7.22	9.85	32.80	36.84	21.11	30.00	-8.89
2	112.52	7.26	10.66	32.80	36.31	21.43	30.00	-8.57
3 pp	117.77	7.29	11.25	32.80	36.08	21.82	30.00	-8.18
4	478.85	8.50	16.50	32.78	26.49	18.71	37.00	-18.29
5	620.71	8.95	19.13	32.88	27.04	22.24	37.00	-14.76
6	848.06	9.34	21.59	32.65	26.67	24.95	37.00	-12.05




7 Photographs

7.1 Conducted Disturbance at Mains Terminals(150kHz-30MHz) Test Setup



7.2 Radiated Disturbance(30MHz-1GHz) Test Setup



7.3 EUT Constructional Details



